

UBC Series Features



UBC Specifications					
Model	Maximum 100AH Front Access Batteries	Maximum 150AH Front Access Batteries	Maximum 170AH Front Access Batteries	Dimensions	Weight
UBC40	30	25		30.5"W x 78.7"H x 31.5"D	450 lbs
UBC52	40	30		36.0"W x 82.0"H x 31.5"D	780 lbs
UBC64	40	40		46.5"W x 82"H x 31.5"D	590 lbs
UBC75			40	48.5"W x 84"H x 33.6"D	1,000 lbs
UBC77	40	40		55"W x 73.8"H x 34.3"D	625 lbs

Cabinet Run Time Table						
Battery Model	Bus Voltage	KWB	Runtime (min)			
			1-string	2-string	3-string	4-string
12AVR100-3ET	360VDC	70	11	33	59	87
12AVR100-3ET		130	2.4	12	24	39
12AVR100-3ET		190		5.9	13	20
12AVR100-3ET		260		2.4	7.4	12
12AVR100-3ET	480VDC	130	5.4	20	39	57
12AVR100-3ET		290		4.2	10	17
12AVR100-3ET		480			3.3	6.8
12AVR100-3ET		720				2.0
HR5500ET	360 VDC	70	26	66	95	144
HR5500ET		130	8.2	30	53	72
HR5500ET		190		16	31	46
HR5500ET		260		8.2	18	30
HR5500ET	480 VDC	130	15	44	72	89
HR5500ET		290		12	25	39
HR5500ET		480			10	17
HR5500ET		720				7.4
HR7500ET	480VDC	210	10.6	36		
HR7500ET		281		23	42	
HR7500ET		469		7.96	19.7	31
HR7500ET		703			7.96	15.8