

Maintenance Bypass

90880 Series Wall Mount Breaker Panel

FEATURES:

- ▶ Available in 14K to 65K AIC ratings
- ▶ Three breaker design (15A-225A)
- ▶ 30-inch wide wall mount design
- ▶ Compact design minimizes footprint
- ▶ Multiple system configurations
- ▶ Optional solenoid key release for added safety



C&CPower offers Wall Mount Maintenance Bypass Breaker Panels available in multiple configurations. The 90880 Series MBBP allows the end user to safely isolate the UPS from utility power and from the load to perform regular service and maintenance. The MBBC contains three Cutler Hammer Series C circuit breakers that are protected by a Kirk Key interlock system.

Our wall mount bypass panels are available in 14K, 35K, or 65K AIC ratings for 480V applications, and 18K, 22K, and 65K AIC ratings for 208V applications. An SKRU (solenoid key release) option is available for added safety.

SPECIFICATIONS:

Voltage: 208 VAC, 3-Phase, 4-Wire
480 VAC, 3-Phase, 4-Wire

Operating Temp: 0° to 40° C (32° F to 104° F)

System Capacity: 15-225 Amperes

Ac Input/Output Terminations: Mechanical lugs are used for both

Wire Size and Type: Per NEC and/or all applicable national and local codes

Specifications		
Style	Dimensions	Weight
90880	30"W x 36"H x 10"D	100 lbs