

Maintenance Bypass

Wall Mount Maintenance Bypass Switch

FEATURES:

- ▶ Multiple system configurations
- ▶ Three modes of operation
- ▶ Make-before-break switching
- ▶ Input and output terminal blocks
- ▶ Durable powder coat finish
- ▶ ETL Listed to UL 1778 and CSA certified



C&C Power's Wall Mount MBS is a three position maintenance bypass switch available in multiple configurations. The MBS allows the user to put the system into three modes of operation. When setting the device to the normal position, utility power is connected to the UPS input. When the switch is set to the test position, the UPS output to the critical load is disconnected while maintaining utility power to the UPS input and to the critical load. When set to the bypass mode, the MBS connects utility power directly to the critical load while removing it from the UPS input.

The MBS utilizes a make-before-break type switch which ensures a connection at all times. The MBS is rated from 40 to 63 amps at 120-208/240 VAC single phase.

Specifications		
Style	Dimensions	Weight
Wall Mount	10.0"W x 14.0"H x 9.0"D	17.8 lbs

Specifications		
C&C Model #	System Volts	System Amps
93802-40	120 VAC Single Phase, 3 Wire	40
93802-50	208/240 VAC Single Phase, 3 or 4 Wire	50
93802-63	208/240 VAC Single Phase, 3 or 4 Wire	63